



Product Service

CERTIFICATE

No. B 09 11 28569 213

Holder of Certificate: Etasis Electronics Corporation

3F, No. 129, Shin-Te Rd.,
241 San Chung City, Taipei Hsien
TAIWAN

Certification Mark:



Product:

**Power supplies
(Redundant Power Supply)**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.:

6121009114901

Date, 2009-11-25

Page 1 of 3

(Bill Lin)

Bill Lin





Product Service

CERTIFICATE
No. B 09 11 28569 213

Model(s): EFRP-Sxx7, EFRP-Sxx7zzzzz,
 EFRP-S2xx7, EFRP-S2xx7zzzzz
 ("xx" can be 30, 40, 50, 60 or 65 to denote
 the output power; "zzzzz" denotes the client ID.,
 it use 0-9, A-Z or a-z and can be 1-5 digits)

Parameters:

Rated inputs:	See attachment
Rated outputs:	See attachment
Protection class:	I
Max. ambient temperature:	50°C
Degree of protection against ingress of liquids:	Ordinary

Remark: When installing, all requirements of below
 mentioned test standards must be fulfilled.

Tested according to: EN 60950-1/A11:2009

Production Facility(ies): 28569, 49209

Bill



Taiwan

The following models of the Redundant Power Supply “EFRP-Sxx7, EFRP-Sxx7zzzzz, EFRP-S2xx7, EFRP-S2xx7zzzzz” will be covered by above certificate:

Model-#	Input Rating	DC Output Rating		
		+12V	+5VSB	Total Wattage
EFRP-S307 EFRP-S307zzzzz EFRP-S2307 EFRP-S2307zzzzz	100-240 Vac, 5 A-2.5A, 47-63 Hz	25 A	3 A	300W
EFRP-S407 EFRP-S407zzzzz EFRP-S2407 EFRP-S2407zzzzz	100-240 Vac, 7 A-3.5A, 47-63 Hz	32 A	3 A	400W
EFRP-S507 EFRP-S507zzzzz EFRP-S2507 EFRP-S2507zzzzz	100-240 Vac, 8 A-4A, 47-63 Hz	41 A	3 A	500W
EFRP-S607 EFRP-S607zzzzz EFRP-S2607 EFRP-S2607zzzzz	100-240 Vac, 10 A-5A, 47-63 Hz	49 A	3 A	600W
EFRP-S657 EFRP-S657zzzzz EFRP-S2657 EFRP-S2657zzzzz	100-240 Vac, 11 A-5.5A, 47-63 Hz	54 A	3 A	650W

Model-#	Input Rating	DC Output Rating						Total Wattage
		+3.3V	+5V	+12V	-12V	+5VSB	+3.3V & +5V combine power	
EFRP-S2307 EFRP-S2307zzzzz	100-240 Vac, 5 A-2.5A, 47-63 Hz	20 A	20 A	24 A	0.5 A	3 A	110 W	300W
EFRP-S2407 EFRP-S2407zzzzz	100-240 Vac, 7 A-3.5A, 47-63 Hz	20 A	20 A	32 A	0.5 A	3 A	140 W	400W
EFRP-S2507 EFRP-S2507zzzzz	100-240 Vac, 8 A-4A, 47-63 Hz	20 A	20 A	38 A	0.5 A	3 A	140 W	500W
EFRP-S2607 EFRP-S2607zzzzz	100-240 Vac, 10 A-5A, 47-63 Hz	24 A	24 A	48 A	0.5 A	3 A	140 W	600W
EFRP-S2657 EFRP-S2657zzzzz	100-240 Vac, 11 A-5.5A, 47-63 Hz	24 A	24 A	53 A	0.5 A	3 A	140 W	650W

Date: 2009-11-25



Testing Laboratory

Bill Lin
Bill Lin