



Product Service

CERTIFICATE

No. B 10 01 28569 215

Holder of Certificate: **Etasis Electronics Corporation**
3F, No. 129, Shin-Te Rd.,
241 San Chung City, Taipei Hsien
TAIWAN

Certification Mark:



Product: **Power supplies**
(Switching Power Supply)

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 612101002801

Date, 2010-01-19
Page 1 of 4

(Bill Lin)

Bill Lin





Product Service

CERTIFICATE
No. B 10 01 28569 215

Model(s): EPAP-S50zzzzz, EPAP-S60zzzzz, EPAP-S70zzzzz,
EPAP-S80zzzzz, EPAP-S56zzzzz, EPAP-S66zzzzz,
EPAP-S76zzzzz, EPAP-S86zzzzz
("zzzzz" denotes the client ID., it use 0-9, A-Z or a-z
and can be 1-5 digits)

Parameters:

Rated input voltage:	100-240 Vac
Rated input current:	See attachment
Rated frequency:	47-63 Hz
Rated outputs:	See attachment
Protection class:	I
Max. ambient temperature:	50°C
Degree of protection against ingress of liquids:	Ordinary

Remark: When installing, all requirements of below
mentioned test standards must be fulfilled.

Tested according to: EN 60950-1/A11:2009

Production Facility(ies): 28569, 49209

Bill L = -



Taiwan

The following models of Switching Power Supply “EPAP-S50zzzzz, EPAP-S60zzzzz, EPAP-S70zzzzz, EPAP-S80zzzzz, EPAP-S56zzzzz, EPAP-S66zzzzz, EPAP-S76zzzzz, EPAP-S86zzzzz” will be covered by above certificate:

Output rating for EPAP-S50zzzzz					
Input rating : AC 100-240V, 47-63Hz, 9A-4.5A					
Voltage (V)	+5V	+3.3V	+12V	-12V	+5VSB
Current (A)	25	25	40	0.8	3.5
Combined Current	40 A				
Total output Power	500 W				

Output rating for EPAP-S60zzzzz					
Input rating : AC 100-240V, 47-63Hz, 9A-4.5A					
Voltage (V)	+5V	+3.3V	+12V	-12V	+5VSB
Current (A)	25	25	48	0.8	3.5
Combined Current	40 A				
Total output Power	600 W				

Output rating for EPAP-S70zzzzz					
Input rating : AC 100-240V, 47-63Hz, 12A-6A					
Voltage (V)	+5V	+3.3V	+12V	-12V	+5VSB
Current (A)	25	25	55	0.8	3.5
Combined Current	40 A				
Total output Power	700 W				

Output rating for EPAP-S80zzzzz					
Input rating : AC 100-240V, 47-63Hz, 12A-6A					
Voltage (V)	+5V	+3.3V	+12V	-12V	+5VSB
Current (A)	25	25	60	0.8	3.5
Combined Current	40 A				
Total output Power	800 W				





Taiwan

The following models of Switching Power Supply "EPAP-S50ZZZZZ, EPAP-S60ZZZZZ, EPAP-S70ZZZZZ, EPAP-S80ZZZZZ, EPAP-S56ZZZZZ, EPAP-S66ZZZZZ, EPAP-S76ZZZZZ, EPAP-S86ZZZZZ" will be covered by above certificate:

Output rating for EPAP-S56ZZZZZ					
Input rating : AC 100-240V, 47-63Hz, 7A-3.5A					
Voltage (V)	+5V	+3.3V	+12V	-12V	+5VSB
Current (A)	25	25	46	0.8	3.5
Combined Current	40 A				
Total output Power	560 W				

Output rating for EPAP-S66ZZZZZ					
Input rating : AC 100-240V, 47-63Hz, 9A-4A					
Voltage (V)	+5V	+3.3V	+12V	-12V	+5VSB
Current (A)	25	25	55	0.8	3.5
Combined Current	40 A				
Total output Power	660 W				

Output rating for EPAP-S76ZZZZZ					
Input rating : AC 100-240V, 47-63Hz, 10A-5A					
Voltage (V)	+5V	+3.3V	+12V	-12V	+5VSB
Current (A)	25	25	63	0.8	3.5
Combined Current	40 A				
Total output Power	760 W				

Output rating for EPAP-S86ZZZZZ					
Input rating : AC 100-240V, 47-63Hz, 12A-6.5A					
Voltage (V)	+5V	+3.3V	+12V	-12V	+5VSB
Current (A)	25	25	71	0.8	3.5
Combined Current	40 A				
Total output Power	860 W				

Date: 2010-01-19



Testing Laboratory

Bill Lin